QuantaMesh BMS T7032-IX7





The Next Wave Enterprise Data Center 100G Switch

- 32 x 100G QSFP28
- x86 CPU Board
- ONIE Pre-loaded

Data center networks face changes with hardware and meeting the requirements of the software it hosts. Quanta Cloud Technology provides a series of Bare Metal Switches, the QCT BMS product line, that addresses these changes in the data center market. The QCT BMS product lines support speeds up to 100G speeds on their Ethernet Switches. To meet the requirements of high performance, high availability, fast scale out, low latency performance, and continuous serviceability in data center applications, the QCT BMS product line is the best choice.

QCT BMS T7032-IX7 supports 32 QSFP28 (10/25/40/50/100GbE speed) in a compact rack unit size. By levering merchant silicon chip, T7032-IX7 is a high performance high density Ethernet switch with advanced features such as smart table, dynamic load balancing, and VxLAN/RIOT support. T7032-IX7 provides programmable capability which allows for future changes such as telemetry & analysis or network overlays & associated metadata. With ONIE (Open Network Installation Environment) pre-loaded it could be used for multiple network operating system which supports ONIE installer to achieve agile installation and fast response for the changing demand.

About QCT

Quanta Cloud Technology (QCT) is a global data center solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation data center design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined data center solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.







Found at: www.QCT.io/wheretobuy

United States

Quanta Cloud Technology USA LLC., Silicon Valley Office

1010 Rincon Circle, San Jose, CA 95131

TOLL-FREE: 1-855-QCT-MUST TEL: +1-510-270-6111 FAX: +1-510-270-6161 Support: +1-510-270-6216

Quanta Cloud Technology USA LLC., Seattle Office

13810 SE Eastgate Way, Suite 190, Building 1, Bellevue, WA

98005

TEL: +1-425-633-1620 FAX: +1-425-633-1621

China

云达科技,北京办公室 (Quanta Cloud Technology)

北京市朝阳区东大桥路 12 号润诚中心 2 号楼

TEL: +86-10-5920-7600 FAX: +86-10-5981-7958

云达科技,杭州办公室 (Quanta Cloud Technology)

浙江省杭州市西湖区古墩路浙商财富中心 4 号楼 501 室

TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式會社

東京都港区芝大門2-5-8 芝大門牧田ビル3F, 105-0012

TEL: +81-3-5777-0818 FAX: +81-3-5777-0819

Germany

Quanta Cloud Technology Germany GmbH

Hamborner Str. 55, 40472 Düsseldorf

TEL: +49-211-74077-300

Korea

QCT Korea, Inc. (주식회사 큐씨티코리아)

서울특별시 영등포구 의사당대로 97 교보증권빌딩 10층, 07327

TEL: +82-10-5397-1412 FAX: +82-2-6336-6710

Singapore

Quanta Cloud Technology Singapore Pte. Ltd.

5 Shenton Way, #10/11-01, UIC Building Singapore, 068808

TEL: +65-6911-6781

Taiwan/ Other Regions

雲達科技 (Quanta Cloud Technology) 桃園市龜山區文化二路211號1樓

1F, No. 211 Wenhua 2nd Rd., Guishan Dist.,

Taoyuan City 33377, Taiwan TEL: +886-3-286-0707 FAX: +886-3-327-0001

Physical Ports

· Port configuration: 32 QSFP28 ports support for 10/25/40/50/100GbE

• Management Port: 1 RJ-45 out-of-band management port (10/100/1000M)

· Console Port: 1 RJ-45 console port

· **USB:** 1 USB 2.0 port

Performance

• **Switching capacity:** 6.4Tbps

· Maximum forwarding rate: 2Bpps

· Latency: Ultra-low latency

· MAC: Unified Forwarding Table to dynamically allocate the L2/L3 tables

Major Components

· ASIC: Broadcom Trident3 BCM56870

CPU: Intel Atom ProcessorsMemory: 8GB DDR3/ECC

· Storage: SSD: 32GB

Mechanical

· Dimension (HxWxD): 43.2x440x508mm

· Weight: 9.78kg(NET)

Environmental Specifications

• Operating temperature: 0~45°C

· Operating humidity: 90% maximum relative humidity

Power

· PSU: 100~240VAC, 50/60Hz, 750W*2 (1+1)

• **Power consumption:** Idle Mode: 217W

Normal Mode: 293W

Safety

· UL, cUL, CB

EMC

· CE. FCC

RoHS

· Reduction of Hazardous Substances (RoHS) 6

Supported Optics and Cables

· DAC cable (QSFP+): 1m, 3m, and 5m

· DAC cable (QSFP+, fan-out): 1m, 3m, and 5m

· DAC cable (QSFP28): 1m, 3m, and 5m

· DAC cable (QSFP28, fan-out): 3m

· AOC cable (QSFP+, 850nm, MMF): 7m and 10m

· AOC cable (QSFP28, 850m, MMF): 1m, 3m, 5m, and 10m

· 40G optic (QSFP+, MPO, 850nm, MMF): 40GBASE-SR4

· 40G optic (QSFP+, LC, 1310nm, SMF): 40GBASE-LR4

 \cdot 100G optic (QSFP28, MPO, 850nm, MMF): 100GBASE-SR4

• **100G optic (QSFP28, MPO, 1310nm, SMF):** 100GBASE-PSM4

· 100G optic (QSFP28, LC, 1310nm, SMF): 100GBASE-LR4

Order Information

· T7032-IX7 (1IX7UZZ0ST4) Front to Back, with Rail Kit

· T7032-IX7 (1IX7UZZ0ST5) Back to Front, with Rail Kit

· PSU - Red (1HY9ZZZ071Y) (F-2-B, AC, 750W)

· PSU - Blue (1HY9ZZZ0720) (B-2-F, AC, 750W)

· FAN Module (1HY9ZZZ0165) (F-2-B)

· FAN Module (1HY9ZZZ0166) (B-2-F)



Intel Inside®. New Possibilities Outside.

Intel, the Intel logo, Intel Inside, Intel Inside logo, Intel Atom and Intel Atom Inside are trademarks of Intel Corporation in the U.S. and/or other countries.

QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders.
Copyright © 2018 Quanta Computer Inc. All rights